

IPPC-4008D

5.7" VGA TFT LCD 4U 19" Half-sized Rack Industrial Panel PC with 8 Expansion Slots & Keyboard Drawer

NEW



Features

- 4U height 19" half-sized chassis with 5.7" VGA display
- Slim keyboard & mouse pad drawer with lockable clip
- Supports high performance Intel Core 2 Duo processors (and up)
- Offers 8 PCI expansion slots
- Lockable front door prevents unauthorized access
- Membrane function keys (F1-F5) for varied application access
- Handy screen function for Industrial Automation Controller and Monitoring
- Front accessible USB is friendly to plug-in versatile USB devices
- All-in-one IPC system for saving cost/space from IPC with LCD/keyboard
- Telecom/Power Station portal and platform for test & measurement equipment
- Suitable for Automatic Testing Equipment and Production Line Testers

Introduction

IPPC-4008D is a 4U 19" half-sized rackmount Industrial Panel PC with 5.7" VGA TFT LCD display, passive backplane and 8 PCI expansion slots. Designed to be an all-in-one and cost-effective solution for traditional IPC users, IPPC-4008D includes a slim type 85 key keyboard and touch pad drawer making input troublefree, and a 5.7" TFT LCD screen is perfect for information displays like: charts, trends, a control panel, simple programming, production data or field monitoring records. A wide range of standard computing peripherals from the Advantech IPC family can be integrated into the unit to meet different application development requirements in mission-critical environments.

Specifications

General

- **Button Control** Membrane Key 5 Function Keys (F1 to F5), 5 Cursor Keys (Up, Down, Left, Right, Enter)
- **Certifications** BSMI, CCC, CE, FCC
- **Dimensions (W x H x D)** 482 x 174.9 x 486.7 mm (18.97" x 6.88" x 19.16")
- **Keyboard Drawer** Integrated 88-Key (US) slim type keyboard w/touch pad
- **Mounting** 19" Rack
- **Power Input** 90 ~ 264 VAC @ 47 ~ 63 Hz full range 6.0/3.0A
- **Power Output** + 5 V @ 30 A, +12 V @ 15 A, +3.3 V @ 28 A, - 5 V @ 0.3 A, -12 V @ 0.8 A, +5 VSB @ 2 A
- **Power Supply** Watt: 300 W, MTBF: 100,000 hrs
- **Weight** 19.99 kg (44 lbs)

System Hardware

- **Passive Backplane** PCA-6108P8
- **Slots** 8 PCI
- **Backplane Size** 315 x 260 mm (12.4" x 10.24")
- **PCI Bridge** Pericom PI7C8150MA
- **PCI Slot** 8 slots
- **Storage** 3 x 5.25" CD-ROM Bay

LCD Display

- **Backlight Life** 50,000 hrs (LED Backlight)
- **Contrast Ratio** 300 : 1
- **Display Size** 5.7"
- **Display Type** VGA TFT LCD
- **Luminance** 220 cd/m²
- **Max. Colors** 262 K (RGB 6-bit)
- **Max. Resolution** 640 x 480
- **OSD Control** ON/OFF, Brightness down, up
- **Viewing Angle (H/V°)** 140/100

Environment


- **Humidity** 5 ~ 85% RH @ 40° C (non-condensing)
- **Ingress Protection** Front panel NEMA4/IP65
- **Operating Temperature** 0 ~ 50° C (32 ~ 122° F)
- **Storage Temperature** -20 ~ 60° C (-4 ~ 140° F)
- **Vibration Protection** 5 ~ 500 Hz, 1 GRMS random vibration (operating)

Ordering Information

- **IPPC-4008D-BOAE** 5.7" VGA 4U 19" IPPC, 300W, 2 PICMG, 10 PCI, 2 ISA

Dimensions


Unit: mm



CPU Card Suggestions

Part No	CPU Grade	Description
PCI-7020VG-00A1E	Intel Core 2 Duo (1066/800/533 MHz FSB)	LGA775 Intel Core 2 Duo PCI Half-size SBC with VGA/GbE LAN/SATA/DVI and SSD (FSB 1066MHz)
PCI-6886F-00A2E	Socket-M Intel Core 2 Duo (667/533 MHz FSB)	PCI Socket479 SlotPC w/LAN/VGA
PCE-3132G2-00A1E	Intel Pentium 4 (400/533/800 MHz FSB)	Socket M Intel Core 2 Duo Half-size SHB with PCIe/VGA/LVDS/Dual GbE LAN (667/533MHz)

System View



Accessories

- **1702002600** Power Cable US Plug 1.8 M
- **1702002605** Power Cable EU Plug 1.8 M
- **1702031801** Power Cable UK Plug 1.8 M
- **1702031836** Power Cable China/Australia Plug 1.8 M

Rear View

