

PPC-157T

15" Panel PC with Intel® Core™2 Duo Processor



Features

- Intel® Core™2 Duo processor up to 2.16 GHz
- System memory up to 4 GB 667 MHz DDR2 SODIMM socket x 2
- One PCI-e Expansion Slot (PCI is available as an option)
- One Mini PCI socket, One Mini PCI-e socket
- Built-in CF card interface (IDE interface for OS booting)
- Dual Gigabit Ethernet ports supporting LAN teaming
- One RS-232/ GPIO (8 channels, TTL level); (by swapping pin header)
- One RS-232/422/485; (supporting Auto-flow control, selecting by BIOS)

Introduction


The PPC-157T is an Intel Core 2 Duo based Panel PC with 15" color TFT LCD. It features multimedia devices, various connectors, and can be installed in virtually any application. In addition, its user-friendly interface makes it a great host for information appliances. Four serial ports and two Gigabit Ethernet ports give the PPC-157T advanced networking capabilities, and provide a great solution for versatile applications.

Specifications

Processor System		CPU	Supports mSocket 478 based Core 2 Duo up to 2.16 GHz	
		CPU FSB	533/667 MHz	
		Chipset	945GME + ICH7M	
		Disk Drive Housing	Room for 1 x 2.5" SATA HDD	
		Dimensions (W x H x D)	396.5 x 317.6 x 103.5 mm (15.6" x 12.5 x 4.08")	
		Weight	6 kg (13.22lb)	
		Front Panel Protection	IP65 compliant	
		HDD	SATA HDD interface (2.5" HDD bay)	
		DVD+/-RW Drive	Optional SATA 8X or above DVD+/-RW Drive, Optional optical drive bay	
		Memory	Supports up to 4 GB of 667 MHz DDR2 SODIMM system memory (socket x 2)	
Network (LAN)		2 x Gigabit Ethernet ports, Wake on LAN, boot from LAN and LAN teaming supported		
I/O Ports		- 4 x COM ports: 2 x RS-232, 1 x RS-232/422/485, - 2 x Gigabit Ethernet ports		
		1 x RS-232/ GPIO (8 channels, TTL level)* - 1 x D-SUB VGA port		
		- 4 x USB 2.0 ports - 1 x PS/2 mouse and keyboard interface		
		- Mic in/ Line out / Line in, 1W speaker - 2 x IEEE 1394 ports (optional)		
		* RS-232/422/485 - selecting by BIOS and supporting Auto-flow control RS-232/GPIO - by swapping pin header		
Environmental Specifications		Bus Expansion	1 x PCI-e Expansion Slot (PCI is available as an option), 1 x Mini PCI socket, 1 x Mini PCI-e socket	
		Operating Temperature	0 ~ 50° C (32 ~ 122° F)	
		Relative Humidity	10 ~ 95% @ 40° C non-condensing	
		Shock	10 G peak acceleration (11 msec. duration)	
		EMC	BSMI, CE, FCC Class B, CCC	
		Safety	CB, CE, UL	
Power Supply	AC Model	Output Rating	150 W (max.)	
		Input Voltage	100 ~ 240 V _{AC} , 50 ~ 60 Hz, 2 ~ 4 A	
		Output Voltage	+3.3 V @ 4.5 A, +5 V @ 8.5 A, +12 V @ 7.0 A, +5 Vsb @ 1.5 A, -12 V @ 0.3 A	
LCD Display		Display Type	Color TFT LCD	
		Size (Diagonal)	15"	
		Max. Resolution	1024 x 768	
		Max. Colors or Grayscales	262K	
		Pixel Pitch (mm)	0.297 x 0.297	
		Luminance (cd/m²)	350	
		Contrast Ratio	400:1	
		Viewing Angle	80° (left), 80° (right), 70° (up), 60° (down)	
		Operating Temperature	0 ~ +50° C	
		LCD MTBF	50,000 hrs	
Touchscreen (optional)		Type	5-wire Analog Resistive (USB interface)	

Dimensions

Unit: mm



Ordering Information

Part No.	Description
PPC-157T-BAREE	15" C2D Based PPC without T/S
PPC-157T-BARE-TE	15" C2D Based PPC with Resistive T/S
PPC-155T STAND	Stand kit for PPC-155/157/175/177 series
PPC-ARM-A03	PPC ARM VESA Standard
PPC-174T-WL-MTE	Wall mount kit for PPC series
1702002605	Power cord 90D 220V EUROPEAN 250V/6A, 1.8M
1702002600	Power cord UL/CSA (USA) 180D 125V/10A 1.83M
989K017700E	Optical disc drive kit for PPC-157/177 (W/O ODD)
989K017702E	DVD-RW (SATA) module for PPC-157/177
989K070601E	PCI riser card for PPC-157/177
989KP15503E	Purchase 802.11a/b/g Mini-PCI Wireless Module for PPC-157/177

Feature Details

Protection

To meet the requirements of a public environment, the front panel PPC-157T complies with the IP65 protection standard. Furthermore, the watchdog timer and power management features make the system secure and stable. The onboard hardware monitoring feature provides an automatic protection function, which prevents the CPU from becoming overheated.


Expansion

To extend functionality, the PPC-157T is designed with one PCI-e expansion Slot (PCI is available as option) and Four USB 2.0 (Universal Serial Bus) ports. With these expansion capabilities, the PPC-157T not only functions as an HMI, but also as a computing center on which to build your applications.

Easy Maintenance

Maintaining and replacing the LCD and touchscreen are made easier through the PPC-157T modular design. In order to replace a defective LCD or touchscreen, one merely needs to remove the front cover and LCD bracket instead of disassembling the entire system.

I/O Appearance



A: Line in/Line out/Mic in
B: PS2 Mouse & Keyboard
C: USB 2.0 x 4
D: VGA Port
E: Power Switch

F: AC Inlet
G: PCI Slot x 1
H: 10/100/1000 Base-T Ethernet x 2
I: RS-232 x 3, RS-232/422/485 x 1