

# eHUB110

Fanless Industrial Grade Powered USB and Powered COM Hub



Front view



Rear view

## Specifications

Standard Color	Silver-black
Construction	Heavy-duty steel
System I/O Outlet	3 x RS-232 (COM 1/2/3), with selectable voltage (+5V, +12V or N/A) 1 x +24V powered USB connector 2 x +12V powered USB connector 1 x +5V powered USB connector 1 x V <sub>oc</sub> power input connector 1 x USB type B connector (host)
System Indicator	1 x green LED for power-on 1 x green LED for USB online 1 x green LED for COM 1 with +5V 1 x green LED for COM 1 with +12V 1 x green LED for COM 2 with +5V 1 x green LED for COM 2 with +12V 1 x green LED for COM 3 with +5V 1 x green LED for COM 3 with +12V
Power Supply	AC 120W Input: 90-264Vac Output: +24V@5A
Operating Temperature	0 °C ~ +50 °C (32 °F ~ 122 °F)
Storage Temperature	-20 °C ~ +80 °C (-4 °F ~ +176 °F)
Humidity	10% ~ 90% , non-condensing
Vibration Endurance	1Grms with HDD (5-500Hz, X, Y, Z directions)
Dimensions	200mm (W) (7.87") x 139mm (D) (5.47") x 40mm (H) (1.57")
Weight (net/gross)	1.5 kg (3.3 lb)/2 kg (4.4 lb)
Certification	CE
EOS Support	XPE, WinCE, Linux

\*W.T.: Wide Temperature. All W.T. supported products have to be sorted by AXIOMTEK.

\*\*XPE: Windows® XP Embedded

## Features



- Supports 3 powered COM with +5V, +12V or without power output
- Supports one +24V, two +12V and one +5V powered USB
- Industrial grade fanless operation design
- Supports +24V DC-in only
- LED indicator for current status

## Packing List

- 1 x Quick manual
- 1 x Driver CD
- 4 x Foot pad
- 1 x USB cable (180 cm)

## Ordering Information

	Standard
eHUB110	Fanless industrial grade powered USB and powered COM hub
	Optional
Power cord	

\*Specifications and certifications are limited to optional.

## Dimensions

