
IFO2175-850-FL (PANEL2175-850-FL)

17" TFT High Performance Fanless Touch Panel Computer with Intel® Core™2 Duo Processor up to 2.53 GHz



Introduction

The IFO2175-850-FL is a slim panel computer equipped with 17-inch 380 nits SXGA LCD display and supports superior Intel® Core™2 Duo/Celeron® M processor. Powered by Intel® GM/GL45 +ICH9M core logic chipset with maximum 256 MB sharing graphics memory, this panel computer has better graphics performance. The panel also supports Dual View and multiple I/O options including 2 USB 2.0 and 3 RS-232 ports. The built-in 1.3 mega pixels camera and microphone/speakers can provide the solution for VoIP, remote monitoring. Furthermore, the IFO2175-850-FL supports antenna for wireless (802.11 b/g) expansion. Besides, the dual Gigabit Ethernet ports can provide the extremely high speed of Ethernet and high reliable redundancy host connection. The IFO2175-850-FL is designed to work with low noise, low power consumption, high

reliability and high performance applications. Besides, excellent $\ensuremath{\mathsf{ID}}$ (industrial design) and user friendly interface design make it perfect with super slim, professional outlook, better user interface, and excellent protection at once! This safe, reliable & user-friendly panel computer can ensure customer's project success and best suited for infotainment, media content display and DSA solutions.

Water/dust-proof design for entire system: IPX1

The IPX1-rating water/dust-proof housing protects the entire system from outside damage of water drip in public place. This unique design improves system stability and save maintenance/re-installation time.

Specifications

Front Bezel	Plastic ABS (Black)	astic ABS (Black)		AMI BIOS with SmartView and customer CMO
LCD Panel	Display Type	17" SXGA TFT		backup
	Brightness (cd/m²)	380 nits	Storage	1 x 2.5" SATA HDD
	Resolution	1280 x 1024	Optical Drive	1 x combo driver (optional)
	Viewing Angle (H/V)	160°/160°	Watchdog	255 levels, 1~255 sec.
Main System	CPU	Socket P for Intel® Core™2 Duo/Celeron® M	Timer	
		processor with FSB 667/800/1066 MHz	Onboard	Integrated in Intel® 945GSE; max. memory
	Chipset	Intel® GM/GL45+ICH9M	Graphics	shared 256 MB
	System Memory	Supports 1 DDR3 SODIMM memory up to 4 GB		

I/O Connectors	2 x RS-232 (COM 1/2)
	1 x RS-232 (COM 3) (optional)
	2 x USB 2.0
	2 x PS/2 mouse and keyboard
	1 x Audio (Mic-in/Line-out)
	1 x VGA
	2 x 10/100/1000Mbps Ethernet
Camera	1 x 1.3 mega pixels camera
Touchscreen	Resistive type
	Light transmission: 80%
	Touch lifetime: 35 million touches
Power Supply	12V∞, with AC-DC power adaptor
Dimensions	437.98mm (17.24") (W) x 76.5mm (3.01") (D)
	x 376.41mm (14.81") (H)
Weight (net/gross)	7.65 kg (16.85 lb)/9 kg (19.84 lb)
Environmental	Operation temperature:
	0°C ~ +40°C (32°F ~ 104°F)
	Relative humidity: 10% ~ 95%, non-condensing
	Shock: 10G peak acceleration (11 sec. duration)
Certification	CE

Ordering Information

IFO2175-850	17" TFT high brightness fanless panel computer with
-FL-AC-CO	resistive T/S, slim combo and camera
IFO2175-850	17" TFT high brightness fanless panel computer with
-FL-AC	resistive T/S (w/o combo and camera)

Optional Accessories

E202003330	VM-101 VESA ARM (clamp type)		
E202003329	VM-105 VESA ARM (wall mount type)		
E222175103	17" stand kit		

Optional OS Installation

/indows [®]	XP	
----------------------	----	--

Touch Panel Computers for Various Industry

Digital Signage and Display

Medical Panel

Medical Grade

GOT Fanless Touch Panel Computers

Touch Panel Computers for Infotainment

Touch Panel Computers for Automation

Touch Panel Monitors for Automation

Dimensions

