


SBC81203

LGA775 Intel® Core™2 Duo PICMG 1.0 Full-size CPU Card with Intel® 945G + ICH7R Chipset, VGA, Audio and Dual LANs

4

Embedded Boards & SoMs



LGA775
Intel® 945G
RS-232/422/485
6 USB 2.0
AC'97 Audio
4 PCI
RAID 0,1,10,5

Features

- LGA775 for Intel® Core™2 Duo/Pentium® D/ Pentium® 4/Celeron® processor with 533/800/1066 MHz
- Intel® 945G + ICH7R chipset
- 2 DDR2 DIMM support up to 4 GB memory
- With Intel® GMA 950 high performance integrated graphics controller
- 4 SATA-300 with RAID 0, 1, 10 and 5

System

CPU	LGA775 socket for Intel® Core™2 Duo/ Pentium® 4/ Pentium®/ Celeron® D/ Celeron® processors with FSB 533/800/1066 MHz
System Memory	2 x 240-pin DIMM supports DDR2-400/533/667 max up to 4GB
Chipset	Intel® 945G + ICH7R
BIOS	Phoenix-Award
SSD	1 x CompactFlash™ type-II socket (optional)
Watchdog Timer	255 levels, 1-255 sec.
Expansion Interface	4 x 32-bit PCI bus masters
Battery	Lithium 3V/220 mAH
Size	338 x 122 mm
Temperature	0° C ~ +60° C (32° F ~ 140° F), operation
Operation Humidity	10% ~ 95% relative humidity, non-condensing

I/O

MIO	1 x IDE; PATA-100 1 x FDD 1 x PS/2 keyboard 1 x PS/2 mouse 1 x LPT; with SPP/EPP/ECP supported 1 x RS-232 (COM 1) 1 x RS-232/422/485 (COM 2)
SATA	4 x SATA-300; with RAID 0/1/10/5
Hardware Monitoring	Detect CPU/system temperature, voltage and fan speed
Ethernet	2 ports as 10/100/1000Mbps support Wake-on-LAN, RPL/PXE Boot ROM with Intel® 82573L
Audio	AC'97 Codec audio as MIC-in/Line-in/Line-out with Realtek ALC203
USB	6 x USB 2.0 ports
SMBus	N/A

Display

Chipset	Intel® GMA 950 graphics Core
Memory Size	Intel® DVM 3.0 compliant
Display Interface	1 x VGA

Packing List

Standard			
Quick installation guide, user's manual/utility CD, cable			
Cable			
Part Number	Description	SBC81203VGGA Qty	SBC81203VGA Qty
59380502000E	COM + Print cable w/ bracket	1	1
59381400000E	FDD flat cable	1	1
59382601000E	Ultra DMA66 IDE cable 40-pin 455mm	1	1
593826A0000E	SATA signal cable 500mm	1	1

Ordering Information

Standard	
SBC81203VGGA	LGA775 socket PICMG 1.0 full-size CPU card (P/N: E381203100) with VGA, 2 10/100/1000Mbps and audio
SBC81203VGA	LGA775 socket PICMG 1.0 full-size CPU card (P/N: E381203101) with VGA, 10/100/1000Mbps and audio
Optional	
E9C900B001	LGA775 P4 cooler3-pin H: 66.8mm
593836A0030E	SATA power cable 4-pin, L=150mm
5938A808010E	2 x USB port cable, L=190mm
59383600000E	Audio cable