


SBC81206

LGA775 Intel® Core™2 Duo PICMG 1.0 Full-size CPU Card with
Intel® 945GC + ICH7/7R Chipset, VGA and Dual LANs



Features

- LGA775 for Intel® Core™2 Duo/Pentium® D/ Pentium® 4/Celeron® processors with 533/800 MHz
- Intel® 945GC + ICH7/7R
- 2 DDR2 DIMM support up to 2GB memory capacity
- With Intel® GMA 950 high performance integrated graphics controller
- ISA with up to 500mA high drive supported

System

CPU	LGA775 socket for Intel® Core™2 Duo/ Pentium® 4/ Pentium®/Celeron® processors with FSB 533/800 MHz
System Memory	2 x 240-pin DIMM supports DDR2-400/533/667 max up to 2GB
Chipset	Intel® 945GC + ICH7/7R
BIOS	Phoenix-Award
SSD	IDE DoM
Watchdog Timer	255 levels, 1~255 sec.
Expansion Interface	4 x 32-bit PCI bus masters 16-bit ISA bus
Battery	Lithium 3V/220 mAh
Size	338 x 122 mm
Temperature	0° C ~ +60° C (32° F ~ 140° F), operation
Operation Humidity	10% ~ 95% relative humidity, non-condensing

I/O

MIO	1 x IDE; PATA-100 1 x FDD 1 x PS/2 keyboard 1 x PS/2 mouse 1 x LPT; with SPP/EPP/ECP supported 1 x RS-232 (COM 1) 1 x RS-232/422/485 (COM 2)
SATA	4 x SATA-300; with RAID 0/1/10/5 (optional with ICH7R)
Hardware Monitoring	Detect CPU/system temperature, voltage and fan speed
Ethernet	2 ports as 10/100/1000Mbps support Wake-on-LAN, RPL/PXE Boot ROM with Realtek RTL8111B
Audio	HD Codec audio as MIC-in/Line-in/Line-out/speaker-out with audio kit AX93242 (optional)
USB	6 x USB 2.0 ports
SMBus	System Management Bus for advanced monitoring/control

Display

Chipset	Intel® GMA 950 graphics Core
Memory Size	Intel® DVMT 3.0 compliant
Display Interface	1 x VGA

Packing List

Standard				
Quick installation guide, user's manual/utility CD and cable				
Cable				
Part Number	Description	SBC81206VGG Qty	SBC81206VGGR Qty	SBC81206VG Qty
59380502000E	COM+Print cable w/ bracket	1	1	1
593826A0000E	SATA signal cable 500mm	1	1	1

Ordering Information

Standard	
SBC81206VGG	LGA775 socket PICMG 1.0 full-size CPU card (P/N: E381206100) with VGA, 2 10/100/1000Mbps
SBC81206VGGR	LGA775 socket PICMG 1.0 Full-size CPU card (P/N: E381206101) with VGA, 2 10/100/1000Mbps and RAID
SBC81206VG	LGA775 socket PICMG 1.0 full-size CPU card (P/N: E381206102) with VGA, 10/100/1000Mbps
Optional	
E9C900B001	LGA775 P4 cooler3-pin H: 66.8mm
5938A808010E	2 x USB port cable, L=190mm
59380000290E	PS/2 keyboard & mouse cable with bracket
E93242100	AX93242-RC HD audio converter kit