
SBC81700

VIA V4 PICMG 1.0 Full-size CPU Card with VGA and Dual LANs



Features



- VIA V4 C7/Eden processors
- VIA CN700+VT8237R-Plus+ITE8888G chipset
- 2 DDR2-400/533 DIMMs support up to 2 GB
- ISA with high drive support up to 500mA

System

CPU	VIA V4 C7/Eden processor with FSB 400MHz	
System Memory	2 x 240-pin DDR2-400/533 DIMMs max. up to 2 GB	
Chipset	VIA CN700+VT8237R-Plus+ITE8888G	
BIOS	Phoenix-Award BIOS	
SSD	N/A	
Watchdog Timer	255 levels, 1~255 sec.	
Expansion Interface	* 32-bit PCI with 3 bus masters	
	* 16-bit ISA with high drive up to 500mA	
Battery	Lithium 3V/196mAH	
Size	338 x 122mm	
Temperature	0°C ~ +60°C (32°F ~ 140°F), operation	
Operation Humidity	10% ~ 95% relative humidity, non-condensing	

1/0

MIO	2 x IDE; PATA-133
	1 x FDD
	1 x PS/2 keyboard
	1 x PS/2 mouse
	1 x LPT; with SPP/EPP/ECP supported
	1 x RS-232 (COM 1)
	1 x RS-232/422/485 (COM2)
SATA	2 x SATA-150
Hardware	Support CPU/System temperature, CPU/System voltage,
Monitoring	and CPU/System fan features
Ethernet	2 ports as 10/100Mbps support Wake-on-LAN, PXE Boot
	ROM with Realtek RTL8100C
	(optional as 10/100/1000Mbps with Realtek RTL8110SC)
Audio	AC'97 Codec audio as MIC-in/Line-in/Line-out/
	Speaker-out with VIA VT1612A (optional)
USB	6 x USB 2.0; 2 ports on the rear I/O, 4 ports with
	pin-header
SMBus	System Management Bus for advanced
	monitoring/control interface

Display

Chipset	Integrated in VIA CN700	
Memory Size	Dedicated up to 64MB frame buffer	
Specifications	VGA up to 1600 x 1200 @ 75 Hz with	
	32-bit color	
Output Interface	VGA with D-sub 15-pin connector	

Packing List

Standard Quick installation guide, user's manual/utility CD, cable Cable					
		Qty	Qty		
59380502000E	COM + Print cable w/ bracket	1	1		
59382601000E	Ultra DMA66 IDE cable 40P 455mm	1	1		
593826A0000E	SATA signal cable 500mm	1	1		

Ordering Information

Standard				
SBC81700VEE-1GE	PICMG 1.0 full-size CPU card with VIA V4			
(P/N: E381700102)	Eden 1 GHz CPU, VGA and 2 10/100Mbps			
SBC81700VE-1GE	PICMG 1.0 full-size CPU card with VIA V4			
(P/N: E381700101)	Eden 1 GHz CPU, VGA and 10/100Mbps			
Optional				
SBC81700VEE-1.5G	PICMG 1.0 full-size CPU card with VIA V4 C7			
(P/N: E381700100)	1.5 GHz CPU, VGA and 2 10/100Mbps			